

TUFFTEAR™ FLOOR BARRIER

TuffTear™ is designed to be a moisture barrier on the bottom side of RV floor frames. With its structural construction it also adds strength and balancing to the floor frame. It is constructed using a tightly woven polyethylene core, and a black poly coating on the face. The backside is a high tensile Kraft linerboard which provides a great surface to adhere to.

Tuff Tear™ is supplied into the RV industry in standard 1000 LnFt/rolls, and standard widths of 96” and 105”. For programs TuffTear™ can be made to customer specific sizes. TuffTear™ is made in the USA and PlyVeneer supplies TuffTear™ from our Springfield, Oregon, Goshen, Indiana, and Red Bay, Alabama warehouses.

SPECIFICATIONS

Base Weight lbs/MSF	TAPPI - T 410	87.5
Caliper - Inches	TAPPI - T 411	0.0245
Color - Top	DOSITM - 003	Black
Moisture Content - %	DOSITM - 005	6.5
Tensile MD - lbs/in	ASTM D 882	155
Tensile CD - lbs/in	ASTM D 882	92

PRODUCT FEATURES

- **Tightly Woven:** The durability of TuffTear is enhanced by its tightly woven polyethylene core, and a black poly coating on the face.
- **High Tensile:** Kraft linerboard which provides a great surface to adhere to.
- **Perfectly suitable for Hot Melt Lamination**
- **Perfectly suitable for Urethane Lamination**
- **Eco-Friendly:** PlyVeneer products are made in the USA from 100% sustainable and responsibly sourced materials.

